


Parallel gripper HGPP-20-A-G2

Part number: 187875

FESTO



Data sheet

Feature	values
Size	20
Stroke per gripper jaw	7.5 mm
Max. replacement accuracy	0.1 mm
Repetition accuracy, gripper	<= 0.02 mm
Number of gripper fingers	2
Mode of operation	double-acting
Gripper function	Parallel
Gripper force back-up	On closing
Design structure	Rack and pinion
Position detection	For inductive sensors For Hall sensors
Operating pressure	5 ... 8 bar
Max. operating frequency of gripper	4 Hz
Min. opening time at 6 bar	62 ms
Min. closing time at 6 bar	58 ms
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further operation)
Corrosion resistance classification CRC	2
Ambient temperature	5 ... 60 °C
Max. force on gripper jaw Fz static	220 N
Max. torque at gripper Mx static	14 Nm
Max. torque at gripper My static	14 Nm
Max. torque at gripper Mz static	14 Nm
Product weight	615 g
Mounting type	with internal (female) thread
Pneumatic connection	M5
Materials note	Free of copper and PTFE
Materials information for cover cap	POM
Materials information, housing	Wrought Aluminium alloy Hard anodised
Materials information for gripper jaws	Wrought Aluminium alloy Nickel plated