
pressure regulator LR-1-D-7-MAXI Part number: 162589 Classic

Modern alternatives can be found by entering the first four characters of the type code in the search field.

With pressure gauge, working pressure up to 7 bar.





FESTO

Data sheet

Feature	Value
Size	Maxi
Series	D
Actuator lock	Rotary knob with lock
Assembly position	Any
Design structure	Piloted piston regulator
Controller function	Output pressure constant
	with secondary exhaust
Pressure gauge	with pressure gauge
Operating pressure	0 16 bar
Pressure regulation range	0.5 7 bar
Max. pressure hysteresis	0.4 bar
Standard nominal flow rate	12,500 l/min
Operating medium	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
	Inert gases
Note on operating and pilot medium	Lubricated operation possible (subsequently required for further
	operation)
Corrosion resistance classification CRC	2 - Moderate corrosion stress
Air purity class at output	Compressed air in accordance with ISO8573-1:2010 [7:4:4]
	Inert gases
Medium temperature	-10 60 °C
Ambient temperature	-10 60 °C
Maritime classification	see certificate
Product weight	1,200 g
Mounting type	Front panel installation
	Line installation
	with accessories
Pneumatic connection, port 1	G1
Pneumatic connection, port 2	G1
Materials note	Conforms to RoHS
Material of connecting plate	Zinc die-casting
Material seals	NBR
Material housing	Zinc die-casting